

5

10

A magnetic recording medium

comprising:

WHAT IS CLAIMED IS

at least one exchange layer structure, and a magnetic layer formed on said exchange layer structure,

said exchange layer structure comprising:

a ferromagnetic layer; and

a non-magnetic coupling layer provided on said ferromagnetic layer and under said magnetic layer,

said ferromagnetic layer and said magnetic layer having antiparallel magnetizations.

20

15

The magnetic recording medium as claimed in claim 1, wherein said ferromagnetic layer is made of a material selected from a group 25 consisting of Co, Ni, Fe, Ni-based alloys, Fe-based alloys, and Co-based alloys including CoCrTa, CoCrPt and CoCpPt-M, where M = B, Mo, Nb, Ta, W or alloys thereof.

30

The magnetic recording medium as claimed in claim 1, wherein said ferromagnetic layer 35 has a thickness in a range of 2 to 10 nm.

4. The magnetic recording medium as claimed in claim 1, wherein said non-magnetic coupling layer is made of a material selected from a group of Ru, Rh, Ir, Ru-based alloys, Rh-based alloys, and Ir-based alloys.

5. The magnetic recording medium as claimed in claim 1, wherein said non-magnetic coupling layer has a thickness in a range of 0.4 to 0.9 nm.

15

6. The magnetic recording medium as claimed in claim 1, wherein said magnetic layer is made of a material selected from a group of Co, and Co-based alloys including CoCrTa, CoCrPt and CoCrPt-M, where M = B, Mo, Nb, Ta, W or alloys thereof.

25

30

7. The magnetic recording medium as claimed in claim 1, which further comprises:
a substrate; and

an underlayer provided above said substrate, said exchange layer structure being provided above said underlayer.

35

5 1/2 4 >

8. The magnetic recording medium as

claimed in claim 7, which further comprises:

a non-magnetic intermediate layer interposed between said underlayer and said exchange layer structure,

said non-magnetic intermediate layer having a hop structure alloy selected from a group of CoCr-M, where M = B, Mo, Nb, Ta, W or alloys thereof, and having a thickness in a range of 1 to 5 nm.

10

15

9. The magnetic recording medium as claimed in claim 8, which further comprises:

a NiP layer interposed between said substrate and said underlayer, said NiP layer being mechanically textured or oxidized.

20

10. The magnetic recording medium as claimed in claim 7, wherein said underlayer is made of a B2 structure alloy selected from a group of NiAl and FeAl.

30

35

25

11. The magnetic recording medium as claimed in claim 1, which comprises at least a first exchange layer structure and a second exchange layer structure interposed between said first exchange layer structure and said magnetic layer, wherein a ferromagnetic layer of said second exchange layer structure has a magnetic anisotropy lower than that of a ferromagnetic layer of said first exchange

layer structure, and magnetizations of the ferromagnetic layers of said first and second exchange layer structures are antiparallel.

5

10

12. The magnetic recording medium as claimed in claim 1, which comprises at least a first exchange layer structure and a second exchange layer structure interposed between said first exchange layer structure and said magnetic layer, wherein a product of a remanent magnetization and thickness of a ferromagnetic layer of said second exchange layer structure is smaller than that of a ferromagnetic layer of said first exchange layer structure, and magnetizations of the ferromagnetic layers of said first and second exchange layer structures are antiparallel.

20

15

A magnetic storage apparatus

25 comprising:

at least one magnetic recording medium including at least one exchange layer structure, and a magnetic layer formed on said exchange layer structure; and

at least one head recording information on and/or reproducing information from the recording medium,

said exchange layer structure comprising:

a ferromagnethe layer; and

a non-magnetic coupling layer provided on said ferromagnetic layer and under said magnetic layer,

35

said ferromagnetic layer and said magnetic layer having antiparallel magnetizations.

5

10

14. The magnetic storage apparatus as claimed in claim 13, wherein said ferromagnetic layer is made of a material selected from a group consisting of Co., Ni, Fe, Ni-based alloys, Fe-based alloys, and Co-based alloys including CoCrTa, CoCrPt and CoCrPt-M, where M = B, Mo Nb, Ta, W or alloys thereof.

15

15. The magnetic storage apparatus as claimed in claim 13, wherein said ferromagnetic 20 layer has a thickness in a range of 2 to 10 nm.

25

16. The magnetic storage apparatus as claimed in claim 13, wherein said non-magnetic coupling layer is made of a material selected from a group of Ru. Rh. Ir. Ru-based alloys. Rh-based alloys, and Ir-based alloys.

30

17. The magnetic storage apparatus as claimed in claim 13, wherein said non-magnetic coupling layer has a thickness in a range of 0.4 to 0/9 nm.

18. The magnetic storage apparatus as claimed in claim 13, wherein said magnetic layer is made of a material selected from a group of Co, and Co-based alloys including coCrTa, CoCrPt and CoCrPt-M, where M = B, Mo, Nb, Ta, W or alloys thereof.

10 All Odds 15

20

5

25

30

35